

PRODUCT SPECIFICATIONS

10 lb. Tool Leash

#5027A

Material Specifications

Webbing: Polyester; Min. 200 lbs. tensile strength

Connectors: Aluminum; WLL = 125 lbs.

Performance Specifications

Tensile Strength: Min. 125 lbs.

Max. Capacity: 10 lbs.

Max. Freefall: N/A

Average Arrest Force: N/A

Max. Elongation: N/A

Relevant Standards

OSHA: N/A

ANSI: N/A

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Not for fall arrest - see user instructions.



This product is manufactured in a manner consistent with the highest standards and best practices of the industry, and is intended to be used to secure tools and personal equipment to protect from falling objects in support of OSHA 1926.300(c), 1926.451(h)(2) and 1926.502(j). There is presently no ANSI standard that pertains to this type of product.

FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.