

PRODUCT SPECIFICATIONS



9' WrapTech Mini Web Self-Retracting Device

74709SA8

Features

- Single -leg SRD for 100% tie-off
- 9' working length
- 3' abrasion-resistant jacketed tie-back legs
- Compact and impact resistant nylon housing
- Integral shock absorber provides visual fall event indication
- Housing swivel-eye reduces lifeline twisting
- 5k Tie-back Carabiner on leg end

Material Specifications

Webbing:	<i>100% Dyneema, 4,500lbs min</i>
Energy Absorber	<i>Polyester</i>
Swivel Eye:	<i>Alloy Steel, 5/8" hole diameter</i>
SRD Housing:	<i>Nylon 6/6</i>
Main Shaft:	<i>Alloy steel</i>
Pawls:	<i>Stainless steel</i>
Leg-end Connector:	<i>Alloy Steel, 5,000lbs min. Static strength with 5,000lbs gate</i>

Performance Specifications (ANSI)

Static Strength:	<i>3,000lbs min.</i>
User Capacity:	<i>310 lbs. max.</i>
Max. Arrest Distance:	<i>54"</i>
Average Arrest Force:	<i>1,125lbs or less</i>
Max. Arrest Force:	<i>1,800 lbs</i>
ANSI SRD Class:	<i>Class B</i>

Relevant Standards

OSHA:	<i>CFR1926.502, CFR1910.66</i>
--------------	--------------------------------

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any signs of activation.
- For use up to Max 5' below the user's dorsal D-ring.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.